


# MATERIAL SAFETY DATA SHEET

#14379

Manufactured by:

**SURFLEX**  
SERIES

**Anderson  
Chemical Company**  
325 SOUTH DAVIS AVENUE  
LITCHFIELD, MINNESOTA 55355  
(320) 693-2477



**Product Name: Lo-Temp Chlorinating Sanitizer**

**24-HOUR EMERGENCY PHONE #: 1-800-424-9300 (CHEMTREC)**

Revised: 11/2/2010 lmt  
Supersedes: 3/3/2000

## I. IDENTIFICATION

### Chemical Name And Synonyms:

Sodium Hypochlorite

### DOT Shipping Name

Hypochlorite Solution

### Chemical Family:

Hypochlorite

### DOT Hazard Class & I.D. Number

Corrosive Material UN1791

# PG

8 III

## II. HAZARDOUS INGREDIENTS

| Component           | CAS NO.   | %    | TLV  | PEL  | Toxic | Hazard               |
|---------------------|-----------|------|------|------|-------|----------------------|
| Sodium Hypochlorite | 7681-52-9 | 5.25 | None | None | NA    | Corrosive / oxidizer |

\*\*Toxic chemical subject to the reporting requirements of Section 313 of the Emergency Planning and Community Right-To-Know Act of 1986 (40 CFR §372).

NA: Not applicable  
NE: Not established

## III. PHYSICAL DATA

**Boiling Point:** 212° F. **Form:** Liquid **pH, 1% Soln.:** 11.4  
**Specific Gravity:** 1.090 **Solubility In Water:** Complete  
**Appearance:** Clear, pale yellow color **Odor:** Chlorine bleach odor

## IV. FIRE AND EXPLOSION HAZARD DATA

**Flashpoint:** Not Applicable

**Extinguishing Media:** Not applicable. Use media for surrounding fire.

**Special Fire Fighting Procedures:** Although this product is not combustible, if a fire occurs in the near vicinity good firefighting practice dictates the use of self-contained breathing apparatus and other protective gear. Cool fire exposed containers with water spray.

**Unusual Fire And Explosion Hazards:** Containers of this material can explode as oxygen is liberated under high heat or fire conditions. Toxic fumes similar to chlorine gas are liberated by contact with acids, ammonia, some detergent cleaners, organic materials, oxidizing agents and some reducing agents. Highly exothermic reactions with organic or oxidizable materials may cause fires in adjacent, heat sensitive materials; Do not

## V. HEALTH HAZARD DATA

**Carcinogenic:** The raw materials used in this product are not considered to be a carcinogen by ACGIH and OSHA.

**Effects Of Over-exposure:** Liquid is irritating to eyes and may damage the eyes. The liquid will irritate the skin, causing redness and possible inflammation, or chemical burns to broken skin. Harmful if swallowed. May cause nausea and vomiting if swallowed. Inhalation causes respiratory tract irritation and irritation of mucous membranes.

**Emergency And First Aid Procedures:** Flush immediately with water for 15 minutes. Lift upper and lower eyelids for complete rinsing. Get immediate medical attention.

**Skin:** Flush with water for 15 minutes. If irritation persists after rinsing, get medical attention. Remove contaminated clothing and wash before reuse.

**Ingestion:** Rinse mouth with water. Give water to dilute. Do not induce vomiting. Get immediate medical attention. Never give anything by mouth to a semi-comatose, comatose, convulsing or unconscious person.

**Inhalation:** Remove victim from immediate source of exposure to fresh air. If breathing is difficult, administer oxygen if available. If victim is not breathing, administer CPR. If individual experiences nausea, headache, or dizziness, get immediate medical attention.

\* NFPA/HMIS Degree or Hazard: 4 = Extreme; 3 = High; 2 = Moderate; 1 = Slight; 0 = Insignificant.

*Continued On Back*

HMIS A. Safety Glasses B. Safety Glasses, Gloves C. Safety Glasses, Gloves, Apron D. Face Shield, Gloves, Apron E. Safety Glasses, Gloves, Dust Respirator F. Safety Glasses, Gloves, Apron, Dust Respirator G. Safety Glasses, Gloves, Vapor Respirator H. Splash Goggles, Gloves, Apron, Vapor Respirator I. Safety Glasses, Gloves, Vapor and Dust Respirator J. Splash Goggles, Gloves, Apron, Vapor and Dust Respirator K. Air Line, Hood or Mask, Gloves, Full Suit, Boots X. Ask your supervisor for guidance.

## VI. REACTIVITY DATA

**Stability - Unstable:**

**Stable: x**

**Conditions To Avoid:** Excessive heat, exposure to light, reduced alkalinity, contamination of any kind. Can result in evolution of chlorine (toxic) gas.

**Incompatibility:** Ether, ammonia, acids, oxidizing agents, reducing agents, oxidizable or combustible materials such as wood, cloth or organic materials, heavy metal such as iron, copper magnesium, aluminum, tin, manganese, zinc, chromium, nickel and their alloys. Mixture with incompatible materials may result in generation of hazardous gases.

**Hazardous Decomposition Products:** HOCL, chlorine, HCl, NaCl, sodium chlorate and oxygen.

## VII. SPILL OR LEAK PROCEDURES

### Steps To Be Taken In Case Material Is Released Or Spilled:

Wear alkali-resistant slicker suit and complete protective equipment including goggles, rubber gloves, rubber boots, and a self-contained breathing apparatus in the pressure demand mode or a supplied-air respirator. If the spill or leak is small, a full facepiece air-purifying cartridge respirator equipped with acid gases/mists filters may be satisfactory. In any event always wear eye protection. For small spills or drips, mop or wipe up and dispose of in DOT-approved waste containers. For large spills, contain by diking with soil or other non-combustible absorbent material and dispose of according to federal or local regulations. Keep non-neutralized material out of sewers, storm drains, surface waters, and soil. This product is very toxic to aquatic life.

**Waste Disposal Method:** Dispose of according to local, state and federal regulations.

## VIII. SPECIAL PROTECTION INFORMATION

**Respiratory Protection:** If recommended exposure limits are exceeded wear: Wear a NIOSH approved respiratory appropriate for the vapor or mist concentration at the point of use.

**Ventilation:** Local mechanical exhaust ventilation to minimize exposure at the point of use.

**Protective Gloves:** Rubber or plastic

**Eye Protection:** Chemical goggles. Face shield if splashing can occur.

**Protective Clothing:** Long sleeved shirt, trousers, rubber boots, rubber gloves, and rubber apron as needed to minimize contact.

## IX. SPECIAL PRECAUTIONS

### Precautions To Be Taken In Handling And Storing:

Store in a cool, dry, well-ventilated place away from incompatible materials. Keep container tightly closed and vented when not in use. Do not use pressure to empty container. Wash thoroughly after handling. Do not get in eyes, on skin, or on clothing. Store in original containers only at temperatures below 85°F. Do not store near acids, oxidizable materials, or organics. Do not store on wooden floors. When empty, the container may still be hazardous. Because containers, even after they have been emptied, still retain product residues, all labeled hazard precautions must be observed.

**Other Precautions** Safety showers and eye wash station should be available in storage and handling areas.

## X. REVISED INFORMATION

**MSDS Status:** MSDS review and update

The opinions expressed herein are those of qualified experts within ANDERSON Chemical Company. We believe that the information contained herein is current as of the date of this Material Safety Data Sheet. Since the use of this information and these opinions and the conditions of use of the product are not within the control of ANDERSON Chemical Company, it is the user's obligation to determine the conditions of safe use of the product.